### **Environmental Protection Agency**

### § 421.207 [Reserved]

# Subpart S—Primary Molybdenum and Rhenium Subcategory

SOURCE: 50 FR 38355, Sept. 20, 1985, unless otherwise noted.

#### § 421.210 Applicability: Description of the primary molybdenum and rhenium subcategory.

The provisions of this subpart are applicable to discharges resulting from the production of molybdenum and rhenium facilities.

#### § 421.211 Specialized definitions.

For the purpose of this subpart the general definitions, abbreviations, and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

#### § 421.212 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitation representing the degree of effluent reduction attainable by the application of the best practicable technology currently available:

(a) Molybdenum sulfide leachate.

BPT LIMITATIONS FOR THE PRIMARY MOLYBDENUM RHENIUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum monthly av- erage
	mg/kg (pounds per million pounds) of molybdenum sulfide leached	
Arsenic	0.968 0.195 0.889 0.570	0.431 0.093 0.588 0.255
Molybdenum	[Reserved]	[Reserved].
Ammonia (as N)	61.720	27.130
Fluoride	16.210	9.214
Total suspended solids	18.980	9.029
pH	(1)	(1)

<sup>&</sup>lt;sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(b) Roaster SO<sub>2</sub> scrubber.

BPT LIMITATIONS FOR THE PRIMARY
MOLYBDENUM AND RHENIUM SUBCATEGORY

Pollutant of pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of molybdenum sulfide roasted	
Arsenic	3.509 0.705 3.224 2.065 [Reserved] 223.800 58.770 68.840	1.561 0.336 2.133 0.924 [Reserved]. 98.390 33.410 32.740

<sup>&</sup>lt;sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(c) Molybdic oxide leachate.

# BPT LIMITATIONS FOR THE PRIMARY MOLYBDENUM AND RHENIUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of molybdenum contained in molybdic oxide leached	
Arsenic Lead Nickel Selenium Molybdenum Ammonia (as N) Flouride Total suspended solids pH	24.210 4.865 22.240 14.250 [Reserved] 1,544.000 405.400 474.900 (¹)	10.770 2.317 14.710 6.371 [Reserved] 678.800 230.500 225.900 (¹)

<sup>&</sup>lt;sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(d) Hydrogen reduction furnace scrubber.

# BPT LIMITATIONS FOR THE PRIMARY MOLYBDENUM AND RHENIUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of molybdenum metal powder produced	
Arsenic Lead Nickel Selenium Molybdenum Ammonia (as N) Fluoride Total suspended solids pH	47.860 9.617 43.970 28.170 [Reserved] 3,052.000 801.400 938.800 (¹)	21.300 4.580 29.080 12.600 [Reserved] 1,342.000 455.700 446.500 (¹)

<sup>&</sup>lt;sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(e) Depleted rhenium scrubbing solution.